



REXTREME™ ROLLER CHAIN

EXTREME PERFORMANCE



- Power transmission in Mechanical Engineering
- Automotive
- Agriculture
- Storage and Material Handling
- Food and Beverage

FEATURES

- · Outstanding tribological characteristics
- · Excellent sliding properties
- High fatigue strength and chain traction force
- Good running-in behavior and improved protection against chain joint stiffness
- Chain sizes with pitch from 12,7 mm to 50,8 mm available
- Corrosion resistance over 120 hours salt spray test
- No process related hydrogen embrittlement during production
- Free from chromium VI
- Dimensions in accordance with ISO and ANSI standards

ADVANTAGES

- Extremely long service life, even without relubrication
- Due to the optimal ex-works lubrication no contamination of conveyed goods and surrounding area occurs
- A very good price performance ratio
- High energy efficiency

LUBRICATION

- Synthetic high-performance long-life lubricant
- Temperature range from 0° C to +120° C
- Free from silicon and Teflon
- On request with special paint compatible lubrication for temperature range -5° C to +250° C or for NSF-H1 requirements available

ReXtreme roller chain is the new standard in Regal Rexnord's

Extreme Performance product portfolio. The excellent properties, due to special manufacturing processes, optimized surface coatings and a well-adhering, moisture-resistant high performance lubrication ensure very good tribological sliding properties and maintenance free operation and suitability for many applications with special requirements.

MAINTENANCE FREE


Due to the high performance and long-life lubrication the need for maintenance and re-lubrication is not necessary anymore. This is ideal in case the maintenance and lubrication possibilities are limited. A special coating in the chain joint offers excellent sliding characteristics.

LONG WEAR LIFE

Whether in conveyor applications, as hoisting chain or as drive chain in general machine building the ReXtreme roller chain is robust and reliable. Re-lubrication is in most drives not necessary, but to protect other components like sprockets, chain guides and so on, it can be done. The performance of the ReXtreme roller chain is not affected.

REXTREMEHIPRO FOR HIGH CORROSION RESISTANCE

For special corrosion protection requirements, the ReXtreme is also available as HiPro version. Advantage of this chain is the outstanding corrosion resistance. The link plates are coated to protect against corrosion and differ also visual from standard roller chain. The special coating from pins or bushings protects against corrosion and stiff chain hinges. The high-performance ex-works long-life lubrication protects the chain during transport, storage and in the application.



Optimum surface hardness for high wear resistance





REXTREME™ ROLLER CHAIN

European Standard - ReXtreme Roller Chain ISO 606

Simplex roller chain

Chain No.	D Pitch		الله Width beetween inner plates	wax, Roller diameter	d₂ max,	wax, p₂ width over inner link	ω Plate depth	Transverse pitch	a ₁ Pin length	connecting sin length	▶ Bearing area	Required minimum tensile strength ISO 606	Rex minimum tensile strength	Average tensile strength	ρ Weight			Loose parts		
	Inch	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm²	N	N	N	kg/m	Α	В	E*	L*	S*
08 B - 1 XT	0.50	12.7	7.75	8.51	4.45	11.30	11.6	-	17.0	20.9	0.50	17 800	18 000	21000	0.7	х	х	х	х	
10 B - 1 XT	0.625	15.875	9.65	10.16	5.08	13.28	14.6	-	19.6	23.7	0.67	22 200	23 800	25 000	0.9	х	х	х	х	
12 B - 1 XT	0.75	19.05	11.68	12.07	5.72	15.62	15.9	-	22.7	27.3	0.89	28 900	29 000	32 000	1.2	х	х	х	х	
16 B - 1 XT	1.00	25.4	17.02	15.88	8.28	25.40	20.5	-	36.1	41.5	2.10	60 000	71 000	80 000	2.7	х	х	х	х	
20 B - 1 XT	1.25	31.75	19.56	19.05	10.19	29.00	25.7	-	40.4	47.6	2.96	95 000	112 000	120 000	3.8	х	х		х	х
24 B - 1 XT	1.50	38.1	25.40	25.40	14.63	37.90	33.0	-	53.8	60.6	5.54	160 000	198 000	211 000	7.0	х	х		х	х
28 B - 1 XT	1.75	44.45	30.99	27.97	15.90	46.50	37.0	-	63.3	72.8	7.39	200 000	200 000	240 000	8.9	х	х		х	х
32 B - 1 XT	2.00	50.8	30.99	29.21	17.81	45.50	41.2	-	65.1	73.6	8.10	250 000	300 000	315 000	9.9	Х	Х		Х	х







cranked link with cotter pin

European Standard - ReXtreme Roller Chain ISO 606

Duplex roller chain

Chain No.	Pitch		Width beetween inner plates	max, toller diameter	Ju diameter d₂ max,	max, width over inner link	m Plate depth	Transverse pitch	a ₁ Pin length	connecting sin length	▶ Bearing area	Required minimum care tensile strength ISO 606	Rex minimum tensile strength	Average tensile strength	D Weight			Loose parts		
	Inch	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm²	N	N	N	kg/m	Α	В	E*	L*	S*
08 B - 2 XT	0.50	12.7	7.75	8.51	4.45	11.30	11.6	13.92	31.0	34.9	1.01	31 100	32 000	38 600	1.4	Х	х	х	х	
10 B - 2 XT	0.625	15.875	9.65	10.16	5.08	13.28	14.6	16.59	36.2	40.3	1.35	44 500	45 200	50 000	1.8	х	Х	х	х	
12 B - 2 XT	0.75	19.05	11.68	12.07	5.72	15.62	15.9	19.46	42.2	46.8	1.79	57 800	58 000	64000	2.3	х	Х	х	х	
16 B - 2 XT	1.00	25.4	17.02	15.88	8.28	25.40	20.5	31.88	68.0	73.4	4.21	106 000	124 000	140 000	5.3	Х	Х	х	х	
20 B - 2 XT	1.25	31.75	19.56	19.05	10.19	29.00	25.7	36.45	76.9	83.6	5.91	170 000	196 000	230 000	7.5	х	х		х	х
24 B - 2 XT	1.50	38.1	25.40	25.40	14.63	37.90	33.0	48.36	102.2	122.7	11.09	280 000	346 000	370 000	13.7	х	х		х	x
28 B - 2 XT	1.75	44.45	30.99	27.97	15.90	46.50	37.0	59.56	122.8	132.7	14.79	360 000	360 000	480 000	17.8	х	х		х	х
32 B - 2 XT	2.00	50.8	30.99	29.21	17.81	45.50	41.2	58.55	123.6	132.4	16.21	450 000	525 000	530 000	19.6	х	х		х	х

^{*} Loose parts are produced in ReXtremeHiPro™ version. Ch




Industrial Powertrain Solutions Regal Rexnord

Contact us: regalrexnord.com/contact

regalrexnord.com

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit https://www.regalrexnord.com/Application-Considerations. To view our Standard Terms and Conditions of Sale, please visit https://www.regalrexnord.com/Terms-and-Conditions-of-Sale (which may redirect to other website locations based on product family).

Regal Rexnord, Rex, ReXtreme and ReXtremeHiPro are trademarks of Regal Rexnord Corporation or one of its affiliated companies.





Chain with straigth sided plates on request.

[&]quot;Regal Rexnord" is not indicative of legal entity